

**D1065S**



## ➔ 6 Zones Standard : WALK THROUGH METAL DETECTOR

Power Supply : AC85 V - 264 V

Working Temperature : -20°C to +50°C

Working Frequency : 4KHZ—8KHZ

Standard Internal size : 1990mm(H)x700mm(W)x  
500mm(Deep)

Standard External size : 2220mm(H)x810mm(W)x  
600mm(Deep)

Package size for door panels : 2260x650x260mmx1ctn

Package size for control unit : 780x390x250mmx1ctn

Gross weight : 70KG

### Features:

- ▶ Six mutual over-lapping detecting zones, Simultaneous alarm from multi-zones
- ▶ Sensitivity adjustable: Each zone has 100 sensitivity level
- ▶ Sound & LED alarm: Both Side LED indicator, easily show where the metal is
- ▶ Automatically count passengers and alarm times
- ▶ Alarm strength indicator on control panel

- ▶ Password protection, only the authorized person can operate
- ▶ Easy assembly: designed with only 2 pieces cables and 8 screws, simply-to-follow instruction
- ▶ Harmless to human body: is harmless with heart pacemaker, pregnant women, magnetic floppy, recording tapes, etc
- ▶ Using high density fireproof material
- ▶ Program Self-diagnostic when power on, no need initial or periodic calibration
- ▶ Modularization design, easy for maintenance and replacement