

D2180S



➔ 18 Zones Standard : WALK THROUGH METAL DETECTOR

Power Supply : AC85 V - 264 V

Working Temperature : -20°C to +50°C

Working Frequency : 4KHZ—8KHZ

Standard External size : 2200mm(H)x800mm(W)x
580mm(D)

Standard Internal size : 2010mm(H)x700mm(W)x
500mm(D)

Package size for door panels : 2260x650x260mmx1ctn

Package size for control unit : 780x390x250mmx1ctn

Gross weight : 70KG

Features:

- ▶ Eighteen mutual over-lapping detecting zones, Simultaneous alarm from multi-Zones
- ▶ Small LCD screen, English operating software, easy to operate
- ▶ Sensitivity adjustable: Each zone has 256 sensitivity level, 0-255 adjustable
- ▶ Sound & LED alarm: Both Side LED indicator, easily show where the metal is
- ▶ Automatically count passengers and alarm times
- ▶ Alarm strength indicator on control panel

- ▶ Password protection, only the authorized person can operate
- ▶ Easy assembly: designed with only 2 pieces cables and 8 screws, simply-to-follow instruction
- ▶ Harmless to human body: is harmless with heart pacemaker, pregnant women, magnetic floppy, recording tapes, etc
- ▶ Using high density fireproof material
- ▶ Program Self-diagnostic when power on, no need initial or periodic calibration
- ▶ Modularization design, easy for maintenance and replacement
- ▶ 4-8 hours backup battery(Optional)