



LIFT UP STYLE QUOTIENT









Finger



RFID



WiFi



LAN



USB



Access Control

### Multi-Bio Attendance and Access Control

## Storage Capacity

Face Capacity	1000
Finger Capacity	10,000
Card Capacity	10,000
Max User	10,000
Password	10,000
Log Capacity	2,00,000

#### **Features**

High-Speed and Accurate Fingerprint Identification


Face, Fingerprint, Card, Password authentication

output relay for door open.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.



# N-BM22 Face

#### Communication Interface

Communication	WIFI, RS485, TCP/IP, USB
---------------	--------------------------

#### **Biometric**

Push Data	YES
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
OS	Linux
Verification Time	<=1 second
RF card options	125kHz EM (Standard) /
	13.56MHz Mifare (Optional)

# Audio/Visual

Display	Capacitive Touch Screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

#### Access control

Wiegand in & out	YES
Relay	YES
Anti Passback	YES
Standard Access Control Function	255 Time Zone, Anti-passback
	Multi-identification Verify mode
Support	RS485 Reader, Wiegand Reader,
	Remote, Push Button, No Touch

### Power & Environment

Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension	190 x 82 x30 Pixels



Auto Focus



low light Verification



Long Distance Verification



Unaffected by High Temperatures 0° **~** 50°

Software

Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Connect with us on

**Disclaimer**: Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

BiomaxOfficial







