



N-BioAccess



Finger











RFID

LAN

USB

Access Control

Fingerprint Time Attendance and Access Control

Storage Capacity

Finger Capacity	10,000
Card Capacity	10,000
Max User	10,000
Password	10,000
Log Capacity	1,50,000



Features

High-Speed and Accurate Fingerprint Identification
Fingerprint, Card, Password authentication
Output relay for door open.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.

N-BioAccess

Communication Interface

Communication WIFI, RS 485, TCP/IP, USB

Biometric

Push Data	YES
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
OS	Linux
Verification Time	<=1 second
RF card options	125kHz EM /
	13.56MHz Mifare (Optional)

Audio/Visual

LCD	2.8" TFT color screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English
Kaypad	Feather Touch Keypad

Access control

Wiegand in & out	YES
Relay	YES
Anti Passback	YES
Support Reader	RS485 Reader, Wiegand Reader,
	Exit Switch, Remote, No Touch

Power & Environment

Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension	190 x 82 x30 Pixels



High-Speed and Accurate Fingerprint Identification



WiFi, RS485, TCP/IP, USB



Unaffected by High Temperatures 0° **~** 50°

Software

Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer: Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.









Connect with us on

BioMax Security



