



SPEEDFACE - 7







Touch Screen



RFIE



WiF



LAN



USB



Access Control

Facial Attendance and Access Control

Storage Capacity

Face ID Capacity	50,000
Max User	50,000
Card Capacity	50,000
Log Capacity	10,00,000



Features

Industrial grade design, with stable performance & smooth line

Detect 5 person at a time

IP42 protection grade.

7-inch IPS display all-sight LCD touch screen.

High end CPU - Dual core ARM cortex - A7 @900MHz

Highly reliable and durable

Recognition speed 0.5 seconds

SpeedFace - 7

Communication Interface

Communication	WIFI, TCP/IP, USB
---------------	-------------------

Biometric

Push Data	YES
Remote firmware update	YES
FAR	0.1%
Accuracy ratio	99.27%
Processor	Dual Core ARM Cortex-A7 @900MHz
OS	Linux
Verification time	<=1 second
Card options	MiFare



Auto Focus



low light Verification





Long Distance Verification



Accepts 5 people at a time

Audio/Visual

LCD	7.0" IPS touch screen display
Shutter type	Electronic Rolling Shutter
Language	English

Software Desktop, Web, Cloud

Access control

Wiegand out	YES
Relay	YES



Time Attendance



Access Control



Employee Self Service



Mobile App

Power & Environment

Operating Temperature	-10°c ~ 50°c
Power	12V DC / 2A
Dimension	247.40 x 127.00 x 24.00 mm

Disclaimer: Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Connect with us on











