



Facial Attendance and Access Control

Storage Capacity

Face ID Capacity	1,00,000
Max User	1,00,000
Log Capacity	10,00,000

Features

Industrial grade design, with stable performance & smooth line

8-inch IPS display all-sight LCD touch screen.

High end CPU - Dual core ARM cortex - A7 @900MHz

Detect human body temperature through face



Speed Face - 8 Temp

"Advance Human body temperature sensor."


SpeedFace - 8 TM

Communication Interface

Biometric

Diometric	
Push Data	YES
Remote firmware update	YES
FAR	0.1%
Accuracy ratio	99.27%
Processor	Dual Core ARM Cortex-A7 @900MHz
OS	Linux
Anti Backlight	YES
Additional Feature	Temperature Measurement

WIFI, TCP/IP, USB





Detect Body Temperature

Audio/Visual

LCD	8.0" IPS touch screen display
Screen Resolution	800 x 1280
Camera Specification	2 MP : 1932 x 1092
Shutter type	Electronic Rolling Shutter
Body Temperature display	YES

Access control

Wiegand out	YES
Living body detection	YES
Relay	YES
Storage	1GB RAM , 8GB ROM

Power & Environment

Operating Temperature	-10°c ~ 50°c
Power	12V DC / 2A
Dimension	126±0.20mm x 469.10±0.20mm x 114.07mm

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Software Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Connect with us on

F	BiomaxOfficial	۲	BioMax Security
0	biomaxsecurity	ín	BioMax Access Contro

